

SEAL CRITICAL AREAS FROM START TO FINISH





THE PROFESSIONAL'S CHOICE FOR CEMENTS & COATINGS

TAMKO has two lines of cements and coatings. Designed for residential, commercial, and industrial use both lines are formulated to provide the right product for the job.





PRIMERS

TAM-Pro® primers are used as a stain barrier, to promote adhesions and to prepare the surface for coating.

PRODUCT		DESCRIPTION AND USES	APPLICATION METHODS	APPROXIMATE COVERAGE*	TECHNICAL PRODUCT INFORMATION [§]	SIZES
813	TAM-Pro Quick-Dry Primer	 <p>A quick-drying low viscosity, pure-asphalt-based material made with penetrating oils and petroleum solvents. Chemically inert to resist mild acids and alkali. Provides a bond to asphalt, concrete, masonry and metal surfaces. Suitable as a bonding agent between the surface and asphaltic cements and coatings used in roofing and waterproofing applications. Adheres to porous and nonporous surfaces to maximize bonding. Coatings applied to this primer may be hot or cold, solvent based or emulsion based. Not for use with coal tar-based materials.</p>	<ul style="list-style-type: none">• Brush• Spray	BUR/Modified roofing—3/4 gallon per 100 sq. ft. Concrete surfaces—3/4 to 2 gallons per 100 sq. ft. Metal surfaces—3/4 gallon per 300 sq. ft.	UL Classified ASTM D41, Type I Miami-Dade County Approved Florida Building Code Approved	10.5 oz. 5 gal.
814	TAM-Pro Low-VOC Asphalt Primer	 <p>A low VOC, pure asphalt-based material made with penetrating oils and petroleum solvents. Suitable as a bonding agent between the surface and asphaltic cements and coatings used in roofing and waterproofing applications. Adheres to porous and nonporous surfaces to maximize bonding. Coatings applied to this primer may be hot or cold, solvent based, or emulsion based. Not for use with coal tar-based materials. Provides a bond to asphalt, concrete, masonry and metal surfaces.</p>	<ul style="list-style-type: none">• Brush• Spray	BUR/Modified roofing—3/4 gallon per 100 sq. ft. Concrete surfaces—3/4 to 2 gallons per 100 sq. ft. Metal surfaces—3/4 gallon per 300 sq. ft.	ASTM D41, Type II Florida Building Code Approved	1 gal. 5 gal.


NON-FIBERED COATINGS

TAM-Pro® & TAMKO® non-fibered coatings are formulated with a thin viscosity to extend the life of your roof and protect the membrane beneath the coating.

PRODUCT		DESCRIPTION AND USES	APPLICATION METHODS	APPROXIMATE COVERAGE*	TECHNICAL PRODUCT INFORMATION [§]	SIZES
845	TAM-Pro Non-Fibered Emulsion Coating	 <p>A versatile coating consisting of a blend of clay, asphalt and water. Provides an additional layer against weathering for asphalt roofing systems or properly prepared metal roofs. Dries to form a surface that resists acid and alkali. Also used as a surface preparation for the application of aluminum roof coating, as well as damp-proofing of concrete and masonry surfaces and ICF (insulated concrete forms).</p>	<ul style="list-style-type: none">• Spray• Roofer's brush	2 to 4 gallons per 100 sq. ft.	ASTM D1227, Type III, Class I Florida Building Code Approved	5 gal.
	TAMKO Non-Fibered Roof Coating	 <p>A thin non-fibered coating for low-slope roofs, as well as metal and masonry surfaces. Steel or wooden fences and underground pipe may also be treated.</p>	<ul style="list-style-type: none">• Brush• Roofer's brush	Per 100 sq. ft.: Composition Roofing: 1 gallon Metal Surfaces: 1/4 gallon		1 gal. 5 gal.
	TAMKO Non-Fibered Roof and Foundation Coating	 <p>A thin-viscosity material that doubles as a non-fibered roof or foundation coating.</p>	<ul style="list-style-type: none">• Brush	Roof coating: 1 gallon per 100 sq. ft. Foundation Coating: 2-Coat Application: 1 gallon covers 75 to 100 sq. ft. per coat		1 gal. 5 gal.
	TAMKO Foundation Coating	 <p>A non-fibered below-grade moisture protection coating. Used for damp-proofing for exterior masonry, concrete and metal surfaces.</p>	<ul style="list-style-type: none">• Brush	2-Coat Application: 1 gallon covers 75 to 100 sq. ft. per coat		5 gal.



FIBERED COATINGS

TAM-Pro® & TAMKO® fibered coatings are formulated with a thicker viscosity to extend the life of your roof and protect the membrane beneath the coating.

PRODUCT		DESCRIPTION AND USES	APPLICATION METHODS	APPROXIMATE COVERAGE*	TECHNICAL PRODUCT INFORMATION [§]	SIZES
829	TAM-Pro Fibered Roof Coating	 <p>A semi-mastic material blended with asphalt, mineral stabilizers, petroleum solvents and fibers. For use on all types of low-sloped roof surfaces, with the exception of coal tar-based materials. Also used on metal, concrete and masonry surfaces. Provides weathering protection for membrane surfaces.</p>	<ul style="list-style-type: none">• Spray• Roofer's brush	BUR/Modified roofing---2 to 3 gallons per 100 sq. ft. Metal surfaces---1 to 1.5 gallons per 100 sq. ft. Concrete/Masonry---3 to 4 gallons per 100 sq. ft.	UL Classified ASTM D4479 Miami-Dade County Approved Florida Building Code Approved	5 gal.



*Subject to manufacturing variation. [§]Tested by an independent laboratory for compliance with ASTM standards where applicable.
Red=TAM-PRO® product produced in Green Cove Springs, FL Blue=TAM-PRO® product produced in Columbus, KS

FIBERED COATINGS (CONTINUED)

PRODUCT		DESCRIPTION AND USES	APPLICATION METHODS	APPROXIMATE COVERAGE*	TECHNICAL PRODUCT INFORMATION [§]	SIZES
829	 TAMKO Fibered Roof Coating	A thick fibered roof coating that seals fine cracks and openings on low-sloped roofs. Can also be used on metal or concrete surfaces.	<ul style="list-style-type: none">• Brush• Roofer's brush	Per 100 sq. ft.: Composition Roofing: 2 to 3 gallons Metal Surfaces: 1 to 1 1/2 gallons Concrete/Masonry: 3 to 4 gallons	ASTM D4479 Florida Building Code Approved	1 gal. 5 gal.
	 TAMKO Fibered Roof and Foundation Coating	A medium viscosity grade fibered material that can be used as a roof or foundation coating.	<ul style="list-style-type: none">• Brush	Roof Coating: 1 to 4 gallons per 100 sq. ft. Foundation Coating: 2-Coat Application: 2 gallons covers 100 sq. ft. per coat	UL Classified ASTM D4479 Florida Building Code Approved	1 gal. 5 gal.




ADHESIVES

TAM-Pro® adhesives are formulated to form a bond with an SBS modified bitumen membrane base and ply sheets.

PRODUCT		DESCRIPTION AND USES		APPLICATION METHODS	APPROXIMATE COVERAGE*	TECHNICAL PRODUCT INFORMATION [§]	SIZES
M3	TAM-Pro Adhesive		An adhesive blended to a smooth, even consistency—applied using a squeegee or spray equipment—containing roofing-grade asphalt and petroleum solvents. Used primarily as the interply roofing adhesive for modified bitumen roofing systems. Also used as an adhesive for granule- or gravel-surface coats.	<ul style="list-style-type: none">• Squeegee• Brush• Spray	Interply—Squeegee/brush: 1.5 to 2 gallons per 100 sq. ft. Interply—Spray: 1.5 to 2.5 gallons per 100 sq. ft. Surface Coat—Granule: 3 to 4 gallons per 100 sq. ft. Surface Coat—Gravel: 5 gallons per 100 sq. ft.		5 gal.
856	TAM-Pro Premium SBS Adhesive		A proprietary formulation consisting of select roofer’s flux asphalt, prime quick-setting VOC-compliant petroleum solvents, minifibers and styrene-butadiene-styrene (SBS) polymers blended to a brush/squeegee-grade consistency. Used to adhere SBS-modified bitumen membranes to the substrate, typically a coated fiberglass base sheet. The substrate to receive the adhesive must be smooth. Irregularities may cause voids, thus inhibiting proper bonding.	<ul style="list-style-type: none">• Squeegee• Brush	1.5 gallons per 100 sq. ft. CGSB 37-GP-56M	UL Classified ASTM D3019, Type III Miami-Dade County Approved Florida Building Code Approved	3 gal. 5 gal.









CEMENTS

TAM-Pro® & TAMKO® cements are formulated to protect and repair flashings and details. Cements provide excellent waterproofing properties for temporary or permanent repairs when used with a variety of TAMKO building products.

PRODUCT		DESCRIPTION AND USES	APPLICATION METHODS	APPROXIMATE COVERAGE*	TECHNICAL PRODUCT INFORMATION [§]	SIZES
	<div>TAMKO</div> <div>TAM-Seal® Roof Patch Sealant Tube</div> <div></div>	An elastic maintenance and repair medium for use of securing shingles and small repair jobs.	<ul style="list-style-type: none">• Caulk gun	25 linear feet with ¼" bead	<div>UL Classified</div> <div>ASTM D4586, Type I</div> <div>ASTM D3409</div> <div>Florida Building Code Approved</div>	10.5 oz.
Q-5	<div>TAM-Pro</div> <div>Heavy-Bodied Flashing Cement</div> <div></div>	A heavy-bodied, all-weather, trowel-grade mastic that contains select asphalts, petroleum solvents, fibers and additives for added spreadability. Dries to form a seal that allows for minor expansion and contraction. Used for flashing construction and other detail roofing work, such as tie-offs or shingle securement. Provides waterproofing properties for temporary repairs, or more permanent repairs when used with glass reinforcement.	<ul style="list-style-type: none">• Putty knife• Trowel	1 gallon covers 12.5 sq. ft. when applied at 1/8" thickness.	<div>UL Classified</div> <div>ASTM D4586, Type I</div> <div>ASTM D3409</div> <div>Miami-Dade County Approved</div> <div>Florida Building Code Approved</div>	3 gal. 5 gal.
Q-10	<div>TAM-Pro</div> <div>Flashing Cement</div> <div></div>	A wet/dry formula flashing cement. Blended from select asphalts, petroleum solvents and fibers to a smooth consistency. For use in flashing construction and other detail roofing work, such as tie-offs or shingle securement. Provides waterproofing properties for temporary repairs, or more permanent repairs when used with glass reinforcement.	<ul style="list-style-type: none">• Putty knife• Trowel	1 gallon covers 12.5 sq. ft. when applied at 1/8" thickness.	<div>UL Classified</div> <div>ASTM D4586, Type I</div> <div>ASTM D3409</div> <div>Miami-Dade County Approved</div> <div>Florida Building Code Approved</div>	3 gal.

*Subject to manufacturing variation. §Tested by an independent laboratory for compliance with ASTM standards where applicable.
Red=Green Cove Springs, FL manufacturing location only

CEMENTS (CONTINUED)

PRODUCT		DESCRIPTION AND USES	APPLICATION METHODS	APPROXIMATE COVERAGE*	TECHNICAL PRODUCT INFORMATION [§]	SIZES
Q-15	TAM-Pro Elastomeric Flashing Cement	 <p>A heavy-bodied wet/dry rubberized mastic cement designed to remain pliable without running. Blended from roofing asphalt, petroleum solvents and interlocking fibers for vital thixotropic properties, and used for vertical and horizontal asphalt roofing flashing systems and waterproofing detail work, such as parapets and drains.</p>	<ul style="list-style-type: none">• Putty knife• Trowel	1 gallon covers 12.5 sq. ft. when applied at 1/8" thickness.	UL Classified ASTM D4586, Type I ASTM D3409 Miami-Dade County Approved Florida Building Code Approved	3 gal. 5 gal.
Q-20	TAM-Pro Premium SBS Flashing Cement	 <p>A heavy-bodied SBS polymer-modified trowel-grade wet/dry formula asphaltic cement. Combines refined asphalt, solvents, wet-surface additives, SBS rubberized polymers and interlocking fibers. Blended into a smooth thixotropic product. May be used for SBS-modified bitumen membrane and built-up roofing flashing applications. Helps prevent, seal or stop leaks around various flashing areas in follow-up maintenance and repair procedures.</p>	<ul style="list-style-type: none">• Putty knife• Trowel• Caulk gun	1 gallon covers 12.5 sq. ft. when applied at 1/8" thickness. 1 tube - ¼" bead, 25 linear feet	UL Classified ASTM D4586, Type I ASTM D3409 Miami-Dade County Approved Florida Building Code Approved	10.5 oz. 3 gal. 5 gal.
801	TAM-Pro Plastic Roof Cement	 <p>A roofing mastic that contains a blend of asphalts, petroleum solvents, fibers and additives that help with spreadability. Dries to form a seal. Used for flashing construction and other detail roofing work, such as tie-offs or shingle securement. Provides waterproofing properties for temporary repairs or more permanent repairs when used with glass reinforcement.</p>	<ul style="list-style-type: none">• Putty knife• Trowel	1 gallon covers 12.5 sq. ft. when applied at 1/8" thickness.	UL Classified ASTM D4586, Type I Miami-Dade County Approved Florida Building Code Approved	
803	TAM-Pro Wet or Dry Surface Plastic Roof Cement	 <p>An all-weather roofing mastic containing modifiers to help enhance bonding to damp surfaces. Made with a mixture of select asphalts, petroleum-solvents, reinforcing fibers and wetting agents that dries to form a seal that allows for minor expansion and contraction. Used for flashing construction and other detail roofing work, such as tie-offs or shingle securement. Provides waterproofing properties for temporary repairs, or more permanent repairs when used with glass reinforcement.</p>	<ul style="list-style-type: none">• Putty knife• Trowel	1 gallon covers 12.5 sq. ft. when applied at 1/8" thickness.	UL Classified ASTM D4586, Type I ASTM D3409 Miami-Dade County Approved Florida Building Code Approved	3 gal. 5 gal.
808	TAM-Pro Cold Application Cement	 <p>A semi-mastic brushing-grade material consisting of pliable asphalt, quick-drying petroleum solvents and fibers (also known as blind-nailing or SIS cement). Blended to set slowly, allowing the roofing membrane to expand, contract and flatten naturally. Serves as an adhesive between plies of 19" selvedge, smooth or mineral-surfaced roll roofing, and laps for cold-applied built-up.</p>	<ul style="list-style-type: none">• Squeegee• Brush	Cold method: 1 gallon covers 50 sq. ft. Lap cement: 1 gallon covers 396 linear ft.	UL Classified ASTM D3019, Type III Miami-Dade County Approved Florida Building Code Approved	3 gal.
801	TAMKO Plastic Roof Cement	 <p>A heavy-bodied plastic roof cement used as a waterproofing medium in new construction and as a general-purpose exterior repair and maintenance material.</p>	<ul style="list-style-type: none">• Putty knife• Trowel	1/8" thickness 1 gallon covers 12.5 square feet	UL Classified ASTM D4586, Type I Florida Building Code Approved	1 gal. 5 gal.
803	TAMKO Wet or Dry Surface Plastic Roof Cement	 <p>Performs as a general-purpose exterior repair and maintenance material on damp or dry surfaces.</p>	<ul style="list-style-type: none">• Putty knife• Trowel	1/8" thickness 1 gallon covers 12.5 square feet	UL Classified ASTM D4586, Type I ASTM D3409 Florida Building Code Approved	1 gal. 5 gal.
	TAMKO Cold Method and Lap Cement	 <p>Multipurpose adhesive for low-sloped, cold applied roof construction. Bonds 19" selvedge, mineral surface roll roofing and capsheets to the underlayment. Doubles as an adhesive on 2" selvedge lap of mineral-, granule- or smooth-surfaced roofing.</p>	<ul style="list-style-type: none">• Brush	Cold Method: 1 gallon covers 50 square feet Lap Cement: 1 gallon covers 396 linear feet	ASTM D3019, Type III Florida Building Code Approved	1 gal. 5 gal.



*Subject to manufacturing variation. §Tested by an independent laboratory for compliance with ASTM standards where applicable.
Red=Green Cove Springs, FL manufacturing location only

NOTICE: THESE PRODUCTS ARE SOLD “AS IS” AND WITHOUT WARRANTY OF ANY KIND. ALL WARRANTIES, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED.

ORDER EVERYTHING YOU NEED IN ONE TRUCKLOAD

Easily order a mixed truckload full of professional-grade materials. From shingles to underlayments to cements and coatings, TAMKO offers a wide range of building products for every part of the project.

SHINGLES

Heritage® Series
Elite Glass-Seal®
MetalWorks®

ACCESSORIES

Ice & Rain Underlayments
Underlayments
Shingle Starter
Cements & Sealants
Ventilation
Hip & Ridge Shingles

WATERPROOFING

Balcony/Breezeway
Specialty Underlayments
Below-Grade
Windows, Doors & Cavity
Thru-Wall



BUILDING PRODUCTS FOR THE PROFESSIONAL

Since 1944, building professionals and homeowners have looked to TAMKO for building products. Today, we offer a wide range of building products, including Heritage® Laminated Asphalt Shingles, Elite Glass-Seal® 3-tab Shingles, MetalWorks® steel shingles, waterproofing materials and ventilation products.



198 Four States Drive
PO Box 97
Galena, KS 66739-0097
1-800-641-4691
tamko.com

©2019 TAMKO Building Products LLC
TAMKO, TAMKO logo, TAM-Pro, TAM-Seal, Elite Glass-Seal,
MetalWorks and Heritage are registered trademarks
of TAMKO Building Products LLC.

Information included in this brochure was current at the time of printing. To obtain a copy of the most current version of this brochure, visit us online at tamko.com or call us at 1-800-641-4691.